


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :		A1	(11) International Publication Number:	WO 99/49680
H04Q 7/22, G08C 17/02, H04M 11/00			(43) International Publication Date:	30 September 1999 (30.09.99)
(21) International Application Number:	PCT/US99/06429			
(22) International Filing Date:	24 March 1999 (24.03.99)			
(30) Priority Data:	60/079,215	24 March 1998 (24.03.98)	US	
(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application	US	60/079,215 (CIP)		
	Filed on	24 March 1998 (24.03.98)		
(71) Applicant <i>(for all designated States except US)</i> :	BELLSOUTH INTELLECTUAL PROPERTY CORPORATION [US/US]; Suite 510, 824 Market Street, Wilmington, DE 19801 (US).			
(72) Inventors; and				
(75) Inventors/Applicants <i>(for US only)</i> :	WHITLEY, Kevin, T. [US/US]; 5030 Oak Hollow Drive, Acworth, GA 30102 (US). WARFEL, Karl, B. [US/US]; 1296 Pinehurst Road, Greysen, GA 30017 (US). SHAND, Arthur, M. [US/US]; 10881 Big Canoe, Big Canoe, GA 30143 (US).			
(74) Agents:	PRATT, John, S. et al.; Kilpatrick Stockton LLP, Suite 2800, 1100 Peachtree Street, Atlanta, GA 30309-4530 (US).			

(S4) Title: WIRELESS TELEMETRY METHODS AND SYSTEMS FOR COMMUNICATING WITH OR CONTROLLING INTELLIGENT DEVICES

(57) Abstract

Methods and apparatus are disclosed for remotely monitoring and controlling via a wireless network various devices deployed in homes and businesses. The present invention allows for monitoring and control of various gateways distributed to remotely located facilities to be monitored and the devices coupled to those gateways to be controlled via a wireless communications network. Preferably, the network is a GSM network adapted to provide short messaging services or any type of wireless network adapted to operate a General Packet Radio System for delivering data over the network. Messages are packaged at each gateway for delivery via the network to a destination terminal, whether a fixed terminal or a mobile station. Likewise, customers may forward data and commands to a particular gateway either from a mobile station or by accessing a fixed terminal, such as through an Internet connection. Transporting messages or commands via the short messaging service of the GSM network or via the GPRS protocol avoids the prohibitive cost of setting up a call for each message and avoids the significant capital costs needed to set up a separate comm



ion network for data delivery.